



TITLE:

# Classification of primitive association schemes with small vertices (Algebraic Combinatorics)

AUTHOR(S):

Hanaki, Akihide; Miyamoto, Izumi

---

CITATION:

Hanaki, Akihide ...[et al.], Classification of primitive association schemes with small vertices (Algebraic Combinatorics).  
数理解析研究所講究録 1999, 1109: 196-200

ISSUE DATE:

1999-08

URL:

<http://hdl.handle.net/2433/63295>

RIGHT:

# Classification of primitive association schemes with small vertices

Akihide Hanaki (花木 章秀、信州大)  
Izumi Miyamoto (宮本 泉、山梨大)

After we intended to give a talk on this title, we have computed a little more association schemes, not only primitive association schemes but also all the association schemes with small vertices. The present result is as follows.

## 1 Association schemes with $n$ vertices, $n \leq 23$

The number of the isomorphism classes of the association schemes.

number of vertices	number of isomorphism classes	
5	3	up to 10 by Nomiyama
6	8	
7	4	
8	21	
9	12	
10	13	
11	4	by Hirasaka
12	59	by Hirasaka
13	6	by Hirasaka and Suga
14	16	by Sakita
15	25	by Hirasaka and Suga
16	222	(Pentium II 400MHz) (SS5 75MHz) (one day) (two weeks*) (a few days) (two weeks) (ten days)
17	5	
18	95	
19	7	
20	95 new	
21	32 new	
22	16 new	
23	21 new	

Let  $(X, \{R_i\}_{0 \leq i \leq d})$  be an association scheme. Let  $A_0, A_1, \dots, A_d$  be its adjacency matrix. Let  $X = \{x_1, x_2, \dots, x_n\}$  be the set of vertices. So  $A_k(i, j) = 1$ , if  $(x_i, x_j) \in R_k$ , 0,

otherwise.

### The property of adjacency matrices

1.  $A_i$  has  $\{0, 1\}$ -entris and has constant collumn and row sum. The sum  $v_i$  is called its *valency*.  $A_0$  =identity matrix.
2.  $A_0 + A_1 + \dots + A_d = J$ (all 1 matrix)
3. For all  $i$  there exists  $i'$  such that  ${}^t A_i = A_{i'}$ .
4.  $A_i A_j = \sum_{0 \leq k \leq d} p_{ijk} A_k$  ( $A_0, A_1, \dots, A_d$  are a basis of the algebra generated by themselves. )

By an association scheme  $A$  we mean the associatin scheme of which relation matrix is  $A$ . Let  $A_i^m = \sum_{0 \leq k \leq d} a_{i,k}^{[m]} A_k$ . Let  $\text{supp}(\langle A_i \rangle) = \{k | a_{i,k}^{[m]} \neq 0 \text{ for some } m \in \{0, 1, 2, \dots, d\}\}$ . An association scheme  $A$  is said to be connected with respect to  $A_i$ , if  $\text{supp}(\langle A_i \rangle) = \{0, 1, 2, \dots, d\}$ . An association scheme  $A$  is *primitive* if and only if  $A$  is connected with respect to  $A_i$  for all  $i \in \{1, 2, \dots, d\}$ . Easy primitive association schemes are

association schemes of class 1 (association schemes with  $d = 1$ ),  
 association schemes with prime vertices, especially, cyclotomic schemes with prime vertices,  
 association schemes defined from primitive permutation groups.

## 2 Primitive schemes with up to 24 vertices

Association schemes of class 1 and cyclotomic schemes with prime vertices always exist, so we omit them. The names of primitive groups are in the library of GAP.

number of vertices	valencies	primitive permutation group
9	1, 4, 4	$3^2:4, 3^2:D8$
10	1, 3, 6	$A(5), S(5)$
15	1, 6, 8	$A(6), S(6)$
	1, 7, 7	non (prim15)
16	1, 5, 10	$(2^4:5).4, 2^4:A_5, 2^4:S_5$
	1, 6, 9	$(A_4 \times A_4):2, 2^4.3^2:4,$ $2^4.S_3 \times S_3, (S_4 \times S_4):2$
	1, 6, 9	non (prim16_1)
	1, 5, 5, 5	$2^4:5, 2^4:D_{10}$
	1, 5, 5, 5	non (prim16_2)
19	1, 9, 9	non (prim19)
21	1, 10, 10	$A(7), S(7)$
	1, 4, 8, 8	$PGL(2,7)$
23	1, 11, 11	non (from prim23_1 to prim23_18)

### 3 Computation, up to 19 vertices

We use group algorithm programming system GAP [7] to compute isomorphism classes of association schemes. Let  $[v_1, v_2, \dots, v_d]$  is the list of valencies arranged in increasing order  $v_1 \leq v_2 \leq \dots \leq v_d$ . The list  $[1', 2', \dots, d']$  indicates the numbers such that  $A_{i'} = {}^t A_i$ . Here we note that always  $v_0 = 1$  and  $0' = 0$ , so they are omitted in the lists. Let  $n$  be the number of the vertices  $|X|$  of an association scheme  $A$ . Then  $[v_1, v_2, \dots, v_d]$  is a partition of  $n - 1$ . We input these two lists  $[v_1, v_2, \dots, v_d]$  and  $[1', 2', \dots, d']$  to our computer program in order to make relation matrices. The following facts show some impossible inputs.

**Proposition 3.1** *There exist no regular graphs of odd valencies with odd vertices, which means that if  $|X|$  is odd and  $v_i = \text{odd}$ , then  $i \neq i'$ .*

**Proposition 3.2** ([3]) *Let  $A$  be an association scheme on a vertex set  $X$ . Let  $n = |X|$  and let  $m$  be the number of valencies such that  $v_i = 1$ . Then the adjacency matrices of valency 1 make a semiregular group on  $X$  and  $m$  divides  $n$ .*

**Proposition 3.3** ([3]) *Let  $m$  be the number of valencies equal to 1. If  $s$  is the number of valencies equal to  $l$ , then  $m$  divides  $sl$ .*

Association schemes of all of its valencies equal to 1 are given by regular representation of groups (cf.[6]). So we omitted to compute this case and relied on the classification of groups. Then we computed all the possible inputs by our GAP-programs to get isomorphism classes of association schemes.

### 4 Computation of primitive schemes

The method of our computation was same as in up to 19 vertices. But we used the following facts and we were able to compute all the possible inputs for the primitive association schemes.

**Proposition 4.1** (cf. [10, Theorem 1.4.2]) *Let  $\mathcal{X}$  be a primitive association scheme. Let  $k$  be the minimal valency greater than 1. Then any prime factor of any valency is less than or equal to  $k$ .*

**Proposition 4.2** *Let  $E$  and  $F$  be disjoint sets such that the union  $E \cup F$  is the set of the valencies of an association scheme  $\mathcal{X}$ . Let  $v_i$  be maximal in  $E$  and let  $v_j$  be minimal in  $E$ . Suppose that any valency  $v_k$  in  $F$  satisfies one of the following.*

- (i)  $v_k$  is coprime with any valency in  $E$  and  $v_j < v_k$ .
- (ii)  $v_k$  is greater than  $v_i v_j$ .

*If  $F$  is not empty, then the association scheme  $\mathcal{X}$  is not primitive.*

We note that many conditions for imprimitivity are given in [1], which are also sufficient for our computation.

We have 271 inputs with 23 vertices. Among them Proposition 4.1 gives 36 inputs  $[[v_1, v_2, \dots, v_d], [1', 2', \dots, d']]$  for primitive schemes and Proposition 4.2 shows 16 of them imprimitive.

For some cases we applied the following argument to prove the imprimitivity. For instance we have cases  $[[v_1, v_2, \dots, v_d] = [3, 3, 4, 6, 6]$  and  $[3, 3, 3, 3, 4, 6]$  imprimitive.

For any adjacency matrix  $A_i$ , define  $A_i^{[0]} = A_0$  and

$$A_i^{[n]} = \begin{cases} A_i^{[n-1]} A_i & \text{if } n \text{ is odd} \\ A_i^{[n-1]} A_{i'} & \text{if } n \text{ is even} \end{cases}$$

Let  $A_i^{[n]} = \sum a_{[n],k} A_k$  and let  $\delta_i(j) = \text{minimum}\{n | a_{[n],j} \neq 0\}$  or  $\delta_i(j) = \infty$  if  $a_{[n],j} = 0$  for all  $n$  ( see [1] Section 5 ).

**Proposition 4.3** (cf. [1] Section 5) *Suppose that  $v_i$  and  $v_j$ , the valencies of  $A_i$  and  $A_j$ , are coprime mutually and that  $\delta_i(j) = n$ . Then  $A_j A_i = p_{j,i,k} A_k$  for some  $k$  with  $\delta_i(k) = n - 1$ , where  $A_i = A_i$  or  $A_{i'}$  if  $n$  is even or odd respectively,  $v_k \geq v_i$ ,  $v_k \geq v_i v_j / (v_i - 1)$  and if the last equality holds, then  $A_k A_{i'} = p_{k,i',m} A_m + v_i A_j$ .*

Proving the above facts, the fundamental property  $p_{ijk} v_k = p_{kj'i} v_i$  plays a most important role. We had not recognized this property well in our computer program.

## 5 Computation, from 20 vertices

There is another fundamental property  $p_{ijk} = p_{j'i'k'}$ . These properties imply that in course of constructing a relation matrix, if one  $p_{ijk}$  is determined, then at the same time  $p_{j'i'k'}$ ,  $p_{k'ij'}$ ,  $p_{i'kj}$ ,  $p_{jk'i'}$  and  $p_{kj'i}$  are determined. We also have conditions that  $p_{ijk} v_k / v_i$  and  $p_{ijk} v_k / v_j$  are integers. As we have checked  $p_{ijk}$  as soon as possible, this improved our program.

## 6 Survey of related topics

Let  $G$  be a transitive permutation group on  $X$ . Then the orbits of  $G$  on  $X \times X$  define an association scheme. For any association scheme  $A$ , each adjacency matrix  $A_i$  can be seen an adjacency matrix of a regular graph, not necessarily connected.

A. Hulpke (1996) computed transitive groups up to degree 30. By Pentium PC 133Mhz, degree 8, 9, 10 take 2 or 3 minutes, degree 12 half an hour, degree 18 or 20 one or 2 days. Up to degree 22 the list is in the library of GAP. (<http://www-gap.dcs.st-and.ac.uk/~ahulpke/publ.html>)

M. Meringer (1996) computed regular graphs by DEC-Alpha UNIX-Workstation and DEC-Station 5000/200. (<http://www.mathe2.uni-bayreuth.de/markus/reggraphs.html>)

## Acknowledgement

The authors wish to thank Dr. Mitsugu Hirasaka for his valuable advices.

## References

- [1] Z. Arad, E. Fisman and M. Muzychuk, *Generalized table algebras*, to appear.
- [2] E. Bannai and T. Ito, *Algebraic Combinatorics I: Association Schemes*, Menlo Park, CA: Benjamin/Cummings, 1984.
- [3] A. Hanaki and I. Miyamoto, *Classification of association schemes with 16 and 17 vertices*, Kyushu J. Math. **52** (1998) 383-395.
- [4] A. Hanaki and I. Miyamoto, *Classification of association schemes with 18 and 19 vertices*, Korean J. Comp. App. Math. **5** (1998) 543-551.
- [5] M. Hirasaka, *The classification of association schemes with 11 and 12 vertices*, Kyushu J. Math. **51** (1997) 413-428.
- [6] E. Nomiyama, *Classification of association schemes with at most ten vertices*, Kyushu J. Math. **49** (1995) 163-195.
- [7] M. Schert, et.al. *GAP – Groups, Algorithms, and Programming*, Lehrstuhl D f Mathematik, Rheinisch Westfälische Technische Hochschule, Aachen, Germany, fifth edition, 1995.
- [8] K. See and S. Y. Song, *Association schemes of small order*, to appear in J. Statist. Plann. Inference. Bose Conference Issue (1998),
- [9] Y. Suga, *Data of association schemes*, published at WWW (July 4, 1996): <http://goldenfish.math.kyushu-u.ac.jp/Suga/ass/class.htm>
- [10] P.-H. Zieschang, *An Algebraic Approach to Association Schemes*, Springer, 1996.